


Diaphragm Metering Pump Makro TZ

Greater safety in continuous operation through mechanically deflected multi-layer safety diaphragm

ProMinent®



Capacity range of single head pump: 260 – 2,100 l/h, 12 – 4 bar

The diaphragm metering pump Makro TZ (TZMb) has an adjustable eccentric drive mechanism and, together with the Makro TZ plunger metering pump, forms a range of drive mechanisms with stroke lengths of 10 and/or 20 mm. A wide range of power end versions is available for use in areas at risk from explosion with ATEX certification.

Your benefits

Excellent process safety and reliability:

- Patented multi-layer safety diaphragm with integral diaphragm rupture warning system.
- Metering reproducibility is better than $\pm 2\%$ within the 30 – 100% stroke length range under defined conditions and with correct installation.

Excellent flexibility:

- The modular construction with single and double head versions permits a wide range of applications, with the double head designs being operated in push-pull mode.
- It is possible to combine up to 4 metering units, even with different pump capacities, in multiple pump systems.
- 5 different gear ratios are available.
- Customised designs are available on request.

Field of application

- Volume-proportional metering of chemicals/additives in water treatment.
- Metering of reactants and catalysts in the chemical industry.
- Level-dependent metering of additives in industrial production engineering.



Diaphragm Metering Pump Makro TZ

Greater safety in continuous operation through mechanically deflected multi-layer safety diaphragm

Technical Data

Type TZMb	With 1500 rpm motor at 50 Hz				With 1800 rpm motor at 60 Hz				Suction lift	Connection, suction/discharge side	Shipping weight PP,NP,TTSS
	Delivery rate at max. back pressure		Max. stroke rate		Delivery rate at max. back pressure		Max. stroke rate				
	bar	l/h	ml/ stroke	Strokes/min	psi	l/h	gph (US)	Strokes/ min	m WC	G-DN	kg
120260	12	260	60	72	174	312	82	86	4.0	1 1/2–25	46/54
120340	12	340	60	96	174	408	108	115	4.0	1 1/2–25	46/54
120430	12	430	60	120	174	516	136	144	4.0	1 1/2–25	46/54
120510	12	510	60	144	174	622	164	173	4.0	1 1/2–25	46/54
120650	12	640	60	180	174	–	–	–	4.0	1 1/2–25	46/54
070430	7	430	99	72	100	516	136	86	3.5	2–32	50/64
070570	7	570	99	96	100	684	181	115	3.5	2–32	50/64
070720	7	720	99	120	100	864	228	144	3.5	2–32	50/64
070860	7	860	99	144	100	1,032	273	173	3.5	2–32	50/64
071070	7	1,070	99	180	100	–	–	–	3.5	2–32	50/64
040840	4	840	194	72	58	1,008	266	86	3.0	2 1/4–40	56/80
041100	4	1,100	194	96	58	1,320	349	115	3.0	2 1/4–40	56/80
041400	4	1,400	194	120	58	1,680	444	144	3.0	2 1/4–40	56/80
041670	4	1,670	194	144	58	2,004	529	173	3.0	2 1/4–40	56/80
042100	4	2,100	194	180	58	–	–	–	3.0	2 1/4–40	56/80

Stroke length 10 mm

Plastic material design: max. 10 bar back pressure

The permissible priming pressure on the suction side is approximately 50% of the max. permitted back pressure

Materials in Contact With the Medium

Liquid end	Suction/discharge connector	DN 25 ball valves			D N 32/DN 40 plate valves **			Valve seats
		Seals	Valve balls	Valve seats	Seals	Valve plates/valve spring		
PPT Polypropylene	PVDF	PTFE	Borosilicate glass	PTFE	PTFE	Ceramic/ Hast. C + CTFE**	PTFE	
PCT PVC	PVDF	PTFE	Borosilicate glass	PTFE	PTFE	Ceramic/ Hast. C + CTFE**	PTFE	
TTT PTFE with carbon	PVDF	PTFE	Ceramic	PTFE	PTFE	Ceramic/ Hast. C + CTFE**	PTFE	
SST Stainless steel mat. no. 1.4404	Stainless steel mat. no. 1.4581	PTFE	Stainless steel mat. no. 1.4401	PTFE	PTFE	Stainless steel 1.4404/Hast. C	PTFE	

Multi-layer safety diaphragms with PTFE coating.

** The valve spring is coated with CTFE (similar to PTFE)

Special versions on request.



Diaphragm Metering Pump Makro TZ

Greater safety in continuous operation through mechanically deflected multi-layer safety diaphragm

Motor Data

Identity code	Power supply	Remarks
S	3-phase, IP 55 220 – 240 V/380 – 420 V 250 – 280 V/440 – 480 V	50 Hz 60 Hz 0.75 kW
R	3-phase, IP 55 230 V/400 V	50/60 Hz 1.5 kW with PTC, speed adjustment range 1:20 with external fan 1-phase 230 V; 50/60 Hz
V0	3-phase, IP 55 230 V ±5 %	50/60 Hz 1.5 kW Variable speed motor with integrated frequency converter
L1	3-phase, II 2G Ex h IIC T3 Gb X	220 – 240 V/380 – 420 V 50 Hz 0.75 kW
L2	3-phase, II 2G Ex db IIC T4 Gb	220 – 240 V/380 – 420 V 50 Hz 0.75 kW with PTC, speed control range 1:5
P1	3-phase, II 2G Ex eb IIC T3 Gb	250 – 280 V/440 – 480 V 60 Hz 0.75 kW
P2	3-phase, II 2G Ex db IIC T4 Gb	250 – 280 V/440 – 480 V 60 Hz 0.75 kW with PTC, speed control range 1:5
V2	3-phase, II 2G Ex de IIC T4	400 V ±10% 50/60 Hz 1.5 kW Ex-variable speed motor with integrated frequency converter

Motor data sheets can be requested for more information. Motors for Sigma basic pumps, special motors or special motor flanges are available on request.

The motors are designed in compliance with the Ecodesign Directive 2009/125/EC.

Information for use in areas at risk from explosion

Only use pumps with the appropriate labelling in line with the ATEX Directive 2014/34/EU in premises at risk from explosion.

Ensure that the explosion group, category and degree of protection specified on the label corresponds to or is better than the conditions prevalent in the intended field of application.

■ SYDNEY OFFICE

Unit 4, 4 Narabang Way,
BELROSE NSW 2085
P 02 9450 0995
F 02 9450 0996
sales@prominentfluid.com.au

■ QUEENSLAND OFFICE

Unit 1, 68 Murdoch Circuit,
ACACIA RIDGE QLD 4110
P 07 3213 1900
F 02 9450 0996
pfcqld@prominentfluid.com.au

■ VICTORIA OFFICE

Unit 1/21-22 National Drive
HALLAM VIC 3803
P 03 8795 7430
F 02 9450 0996
pfcvic@prominentfluid.com.au

■ WESTERN AUSTRALIA OFFICE

Office 11, 34 Welshpool Road
WELSHPOOL WA 6106
pfcwa@prominentfluid.com.au